



WAV technical Specification

(All dimensions minimum and maximum for model range approved)

Wheelchair Access Entrance Dimensions

	Variant / Version	
Width (mm)	760 with Fiorella Lift 605 with AMF Lift	
Height (mm)	1177 1214 With Extended Roof Scoop	

Designated Travelling Position (add table / extend table as necessary)

	Variant / Version	
Width (mm) (min and max)	585	
Length (mm) (min and max)	1210	
Wheelchair space gradient (°)	0.2	
Maximum seated eyeline height (mm)	1184	
Internal roof height (mm)	1345	
Maximum wheelchair mass (kg)	85	

Maximum access dimensions (add table / extend table as necessary)

	Variant / Version	
Width (mm)	605 Fiorella Lift 720 AMF Lift	
Length (mm)	1210	
Height (mm)	1177	

Lift platform (if fitted)

	Variant / Version	
	Fiorella Lift	AMF Lift
Width (mm)	760	730
Length (mm)	1090	1400
Safe working load (kg)	250	400

Winch (where fitted)

Variant / Version



Safe working load		

WAV

	Variant / Version	
Maximum permitted front axle mass (kg)	Variant Dependant: 1490-1550	
Maximum permitted rear axle mass (kg)	Variant Dependant: 1490-1750	
Gross vehicle mass (kg)	Variant Dependant: 2800-3200	
Kerb mass (kg)	2727-2782	
Fuel tank capacity (litres)	OEM	
Ground clearance (mm)	Over 120	

Seating provisions

	Variant / Version	
Maximum number of designated wheelchair positions	1	
Up front wheelchair position?	No	
Maximum number of seating positions (inc. driver)	4	
Spare wheel or puncture repair kit?	Puncture Repair	

Details of any limitations on seating capacity when carrying wheelchairs:

Variant / Version	

Notes: N/A

(1) Delete as appropriate

